NEW ENGLAND BRICK



Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to New England Brick

Standard Colors: Charleston, Chesapeake Bay, Dakota Brown, Roxbury or Any Custom Color

Grout Joint Width: 1/2" Grout Joint

Grouting Options: Deep Raked, Full Brushed or Full Tooled

Grout Joint Color: Natural Grey, Natural Off-White or Complementary Color

Accessories: Corners, Complementary Tiles, Wall Caps and more. (See Accessories section of binder)

Special Installation Notes

Pattern: Do not install bricks vertically. Blend the bricks on the wall from several different boxes to ensure proper color and

size variation. See catalog photos for recommended installation pattern.

Chalk Lines: Should be used by installer to ensure a straight and level pattern.

Sealing: Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we

suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.

Freeze-Thaw: When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar

on the back of each stone, which will prevent water pooling behind the stone after it's been installed.

Installation Info: Download Coronado's latest installation instructions at www.coronado.com for information on mortar and

installation recommendations.

Profile Properties

Size: Brick size is 2%" ($\pm \frac{1}{16}$ ") in height and $9\frac{1}{2}$ " ($\pm \frac{1}{8}$ ") in length (nominal).

Thickness: 1/2" (±1/16")

Weight: 4 to 6 lbs. per square foot.

Packaging: Available in a brick box (15 sq ft Flats & 9 lft Corners). When purchasing New England Brick, coverage is

based on installation with a 1/2" joint.

1/2" Smooth Tooled Grout Joint



New England Brick Color: Charleston

1/2" Smooth Brushed Grout Joint



NEW ENGLAND BRICK

COLOR: DAKOTA BROWN